



TRANSIT BIKE RACKS	APEX 3	TRILOGY	APEX 2	DL2	DL2 NP	BIKE TRAILER
RACK SPECIFICATIONS	3-POSITION BIKE RACKS		2-POSITION BIKE RACKS			12 OR 16 BIKES
LENGTH ¹	35"	31"	30"	28"	28"	180"/233"
WIDTH	83"	96"	60"	65"	55"	76"
STATIC WEIGHT	65 LBS	53 LBS	44 LBS	36 LBS	35 LBS	600/700 LBS
LIFTING WEIGHT	15 LBS (1 SPRING)	12 LBS (2 SPRINGS)	19 LBS	19 LBS	19 LBS	N/A
MAX CARRYING WEIGHT	165 LBS (55 LBS/BIKE)	165 LBS (55 LBS/BIKE)	110 LBS (55 LBS/BIKE)	110 LBS (55 LBS/BIKE)	110 LBS (55 LBS/BIKE)	N/A
FRAME CONSTRUCTION	STAINLESS STEEL	STAINLESS/MILD STEEL	STAINLESS STEEL	STAINLESS/MILD STEEL	STAINLESS/MILD STEEL	STAINLESS STEEL
WHEEL TRAY MATERIAL	STAINLESS STEEL	STAINLESS/MILD STEEL	STAINLESS STEEL	STAINLESS/MILD STEEL	STAINLESS/MILD STEEL	STEEL
MODULAR TRAY ²	YES	NO	YES	OPTIONAL	NO	NO
FAT TIRE OPTION AVAILABLE ³	YES	NO	YES	NO	NO	NO
RECOMMENDED USE	FRONT BUMPER	FRONT BUMPER	FRONT BUMPER	FRONT BUMPER	FRONT BUMPER	RECEIVER HITCH
102" WIDE VEHICLES	OK	OK	OK	OK	OK	OK
96" WIDE VEHICLES	OK	NOT RECOMMENDED	OK	OK	OK	OK
LESS THAN 96" WIDE VEHICLES	NOT RECOMMENDED	NOT RECOMMENDED	OK	OK	OK	N/A
AVAILABLE FINISHES ⁴	AG OR PC	AG OR PC	AG OR PC	AG OR PC	AG OR PC	ZE
AVAILABLE LABELS	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL
BIKE SPECIFICATIONS						
CARRYING CAPACITY	3 BIKES	3 BIKES	2 BIKES	2 BIKES	2 BIKES	12 OR 16 BIKES
MAX TIRE WIDTH ³	3.25" / 5.5"	2.25"	3.25" / 5.5"	2.25"	2.25"	2.75"
MAX WHEELBASE	48"/51"	44"	48"/51"	44"	44"	48"
WHEEL DIAMETER	16" - 29"	20" - 29"	16" - 29"	20" - 29" ⁵	20" - 29"	20" - 29"
MAX BICYCLE WEIGHT	55 LBS	55 LBS	55 LBS	55 LBS	55 LBS	55 LBS

NOTES:

¹ Length is measured outwards from the front mask of the vehicle starting at the back of the pivot plate to the front edge of the bike rack.

² Modular racks with removable wheel trays allow damaged and worn out parts to be replaced, resulting in lower maintenance costs.

³ Fat Tire Bike Option is now available for Apex 2 and Apex 3 racks and accommodates fat bike tires up to 5.5" in width and is backwards compatible with standard tire widths.

⁴ Abbreviations: Anti-Glare = AG, Powder Coat = PC, Zinc undercoat with Epoxy paint = ZE. Powder Coating is available in black, white, gold, red, safety yellow and custom colors upon request.

⁵ 16" compatible support arms are available as an option.



TRANSIT BIKE RACKS	ANGLED HOOK	INTERLOCK	SWINGLOCK	SPINLOCK	UPRIGHT	UNIVERSAL
RACK SPECIFICATIONS	VERTICAL			HORIZONTAL		LUGGAGE BAY
LENGTH	32"	12.75"(VARIES)	28"	26.5"	60"	91.9"
WIDTH	82"	7.25" (VARIES)	10.5"	7.25"	10.5"	43.6" X 19"(H)
MIN SPACING	15"	26"	15" ¹	16" ¹	26"	N/A
STATIC WEIGHT	16.5 LBS	21 LBS	12 LBS	12 LBS	12 LBS	280 LBS
LIFTING WEIGHT	N/A	N/A	N/A	N/A	N/A	20 LBS
MAX CARRYING WEIGHT	55 LBS	55 LBS	55 LBS	55 LBS	55 LBS	N/A
FRAME CONSTRUCTION	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL
WHEEL TRAY MATERIAL	N/A	N/A	N/A	N/A	N/A	N/A
MODULAR ²	NO	NO	NO	NO	NO	NO
RECOMMENDED USE	BUS/RAIL INTERIOR	BUS/RAIL INTERIOR	BUS/RAIL INTERIOR	BUS/RAIL INTERIOR	LUGGAGE BAY	LUGGAGE BAY
102" WIDE VEHICLES	OK	OK	OK	OK	OK	OK
96" WIDE VEHICLES	OK	OK	OK	OK	OK	N/A
LESS THAN 96" WIDE	OK	OK	OK	OK	OK	N/A
AVAILABLE FINISHES ³	AG	AG	AG	AG	AG	PC
AVAILABLE LABELS	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL	BILINGUAL
BIKE SPECIFICATIONS						
CARRYING CAPACITY	1 BIKE	1 BIKE	1 BIKE	1 BIKE	1 BIKE	2 BIKES
MAX TIRE WIDTH	3"	2.5"	3"	2.75"	2.5"	N/A
MAX WHEELBASE	48"	48"	48"	44"	44"	48"
WHEEL DIAMETER	16"- 29"	16"- 29"	16"- 29"	20"- 29" ⁴	20"- 29"	16"- 29"
MAX BICYCLE WEIGHT	55 LBS	55 LBS	55 LBS	55 LBS	55 LBS	55 LBS

NOTES:

¹ Racks require vertical stagger

² Modular racks with removable wheel trays allow damaged and worn out parts to be replaced, resulting in lower maintenance costs.

³ Abbreviations: Anti-Glare = AG, Powder Coat = PC, Zinc undercoat with Epoxy paint = ZE. Powder Coating is available in black, white, gold, red, safety yellow and custom colors upon request.

⁴ Floor mounted Spinlock will fit 20"-29" wheel diameter, raised Spinlock variations will fit 26"-29" wheel diameter.