

Guide Specifications for Public Work Stand**SECTION 02871 OR MASTERFORMAT (2004) SECTION 129313 - BICYCLE RACKS****Part 1 General****1.01 Summary**

- A. This section includes specifications for the Public Work Stand

1.02 Related Sections

- A. Related Requirements:
 - i. Section 12 93 14- Bicycle Lockers: Enclosed bicycle storage lockers.
 - ii. Section 32 39 13 – Bollards: Bollards with bicycle storage.
- B. American International (ASTM):
 - i. ASTM A 53 - Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless.
 - ii. ASTM A 123 - Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products.
 - iii. ASTM A 312 - Standard Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless Steel Pipes.
 - iv. ASTM A 314 - Standard Specification for Stainless Steel Billets and Bars for Forging.

1.03 Submittals

- A. Product Data: Manufacturer's data sheets on each product to be used, including full range of standard color selections.
- B. Maintenance Data: Manufacturer's installation and maintenance guide.
- C. Samples for Verification: Submit finish samples for review and verification.
- D. Include recommended methods for repairing damage to the finish.

1.04 Quality Assurance

- A. Manufacturer Qualifications: A firm experienced in manufacturing bicycle repair equipment similar to that required for this project and with a record of successful in-service performance.
- B. Installer Qualifications: An experienced installer who has completed installation of bicycle repair equipment similar in material, design, and extent to that indicated for this project and whose work has resulted in construction with a record of successful in-service performance.
- C. Source Limitations: Obtain each color, finish, shape and type of bicycle repair equipment from a single source with resources to provide components of consistent quality in appearance and physical properties.
- D. Product Options: Drawings indicate size, shape and dimensional requirements of bicycle repair equipment and are based on the specific system indicated.

1.05 Delivery, Storage and Handling

- A. Deliver all materials in their original sealed containers bearing manufacturer's name and identification of product.
- B. Do not store products in location with conditions outside manufacturer's absolute limits.
- C. Materials delivered to the site shall be examined for concealed damage or defects in shipping. Defects shall be noted and reported to the Owner's Representative in writing.

1.06 Project Conditions

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.

1.07 Warranty

- A. The Public Work Stands carries a one year manufacturer's limited warranty against defects in materials and workmanship. The warranty period begins the date the product is shipped from the manufacturer.

Part 2 Products

2.01 Manufacturer

- A. Provide bicycle repair equipment manufactured by Saris Infrastructure, and distributed by Sportworks Northwest, Inc. Phone: 425-483-7000. Website: www.sportworks.com
- B. Substitutions: Not permitted.
- C. Requests for substitutions will be considered in accordance with provisions of Section 01 60 00 - Product Requirements.

2.02 Design

- A. Pedestal upright repair stand.
- B. Nine common bicycle tools tethered by stainless steel aircraft cable.
- C. ADA Compliant.

2.03 Materials

- A. Main body and hanger:
 - i. 2" DOM tubing
 - ii. .25" steel plate
 - iii. Polyethylene sleeve
- B. Tool Tethers:
 - i. 3/16" stainless steel cable
- C. Tools
 - i. Phillips screwdriver with swivel
 - ii. Flat blade screwdriver with swivel
 - iii. Steel core tire lever (qty 2.)
 - iv. Headset wrench
 - v. Pedal wrench
 - vi. 8/10mm cone wrench
 - vii. 9/11mm cone wrench
 - viii. Torx T25 wrench
 - ix. 2.5, 3, 4, 5, 6, 8mm Hex keys

2.04 Finishes

- A. Powdercoat finish: TGIC UV resistant Powdercoat.
 - i. Color Option: Black RAL9017
 - ii. For powder coated/ painted Public Work Stands, the following specifications are required: Part is prepared for painting with hard sandblasting. An epoxy primer is electrostatically applied. A final TGIC, UV resistant polyester powder coat is applied. Final coating thickness shall be no less than 6 mils.

2.05 Setbacks and Space Use

- A. Follow setbacks and space use in accordance with manufacturer's site layout document.

Part 3 Execution

3.01 Examination

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.02 Installation

- A. Install the Public Work Stand in accordance with manufacturer's installation instructions.
- B. Install the Public Work Stand level, plumb, square, accurately aligned, correctly located per drawings, and without warp.
- C. It is the responsibility of the installer to ensure that all base materials into which the Public Work Stand will be installed can support the public work stand and will not be damaged by any required installation procedures.

3.03 Ordering Information

- A. When ordering or specifying the Public Work Stand, make sure the product type, finish and fastener type (if applicable) are included. Contact your Sportworks Northwest Inc. representative for a current price list or to place an order.

3.04 Protection

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.