

SPINLOCK

FOR RAIL AND BUS RAPID TRANSIT



HORIZONTAL PARKING: The simple roll in design creates an effortless parking solution with no lifting required.

MOUNTING RISERS: Purposefully engineered risers that can be easily installed at variable heights which eliminates handlebar interference.

ONE-WAY ROLLER: The ratcheting roller provides unparalleled bicycle retention along with ease of loading.



INTERIOR BIKE RACKS

INTERLOCK

SWINGLOCK

SPINLOCK

RACK SPECIFICATIONS

HEIGHT ¹	72"	65"	29" / 33" / 52.5"
WIDTH ²	8"	9"	7"
STATIC WEIGHT ³	26.5 LBS	13.2 LBS	12.0 LBS / 17.2 LBS / 23.5 LBS
FRAME CONSTRUCTION	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL
WHEEL TRAY MATERIAL	STAINLESS STEEL	STAINLESS STEEL	STAINLESS STEEL
RECOMMENDED USE	CAR INTERIOR	CAR INTERIOR	CAR INTERIOR
102" WIDE CARS	STANDARD	STANDARD	STANDARD
96" WIDE CARS	STANDARD/ANGLED	N/A	STANDARD/ANGLED
AVAILABLE FINISHES	ANTI-GLARE	ANTI-GLARE	ANTI-GLARE
AVAILABLE LABELS	ENGLISH	ENGLISH	ENGLISH

BIKE SPECIFICATIONS

CARRYING CAPACITY	1 BIKE	1 BIKE	1 BIKE
MAX TIRE WIDTH	2.5"	3.0"	2.75"
MAX WHEELBASE	48"	48"	N/A
WHEEL DIAMETER	16"-29"	16"-29"	26"-29"
MAX BIKE WEIGHT ⁴	N/A	N/A	N/A
BICYCLE LIFT REQUIRED	YES	YES	NO

NOTES:

¹ HEIGHT IS MEASURED WITH THE RACK INSTALLED AND INCLUDES UPPER AND LOWER UNIT, SPINLOCK INCLUDES FLOOR MOUNT, 14.0" RISER, AND 23.5" RISER

² WIDTH IS MEASURED WITH THE RACK INSTALLED AND DOES NOT INCLUDE THE BICYCLE

³ WEIGHT FOR SPINLOCK SHOWN FOR FLOOR MOUNT / 14.0" RISER / 23.5" RISER WITH RAMP

⁴ BICYCLE MAXIMUM WEIGHT IS LIMITED BY THE ABILITY OF THE USER TO LIFT THE BICYCLE